SHAMROCK

Technical Data

FluoroSPERSE® 966

PTFE Dispersion

Shamrock offers dispersions of PTFE that may be poured directly from the drum into the mixing container. They assure good wetting, uniform composition, and avoid the handling of powder. They are available in a range of printing ink vehicles, solvents, and in combination with wax.

Product Description:

FluoroSPERSE® 966 is a finely micronized polytetrafluoroethylene (PTFE) dispersion in a petrolatum and soya alkyd drying oil.

Application:

FluoroSPERSE® 966 is recommended for offset and heat set inks at 2-4% of the total formula weight.

Features and Benefits:

- Rub and Abrasion Resistance
- Slip (Low COF)
- High Temperature Resistance
- Scratch Resistance
- Ease of Incorporation

Typical Properties:

NPIRI Grind:	2.5 Max
Weight/Gallon:	11.2 – 11.3 Lbs / Gal

Regulatory Status:

The components of this product are listed on multiple chemical inventories. For specific information on the applicable chemical inventories, please refer to the product SDS.

Safety, Shipping and Handling:

For complete safety, shipping and handling information please contact your regional Customer Service Representative, or our Customer Service Team at customerserviceteam@shamrocktechnologies.com.

For **more** information about Shamrock's other products or capabilities please visit us at our website, ShamrockTechnologies.com.

Corporate Headquarters
Foot of Pacific Street
Newark, NJ 17114
Phone: +1(800)349-1822

Henderson, KY
301 Community Drive
Henderson, KY 42420
Phone: +1(800)349-1822

Tongeren, Belgium
Heersterveldweg 21,
B-3700 Tongeren Belgium
Phone: +32 1245 8330

Tianjin, China
Fty 5, Ave. 9, TEDA
Phone: +86 22 5981 3085

The information contained in the technical data sheet is to the best of our knowledge, true and accurate. However, no warranty is expressed or implied regarding the accuracy of the data. The results to be obtained from the use thereof, or that any such use will not infringe any patent.

Issue Date 11-16-2017