

**RESIFLOW® L-66F  
FLOW CONTROL AGENT  
FOR THE COATINGS INDUSTRY**



THE EDGE OF INNOVATION

[www.estron.com](http://www.estron.com)

**GENERAL DESCRIPTION**

Resiflow L-66F is a high viscosity, carboxyl functional polyacrylate flow control agent. It can be used in a variety of coating systems and provides exceptional clarity in clearcoat systems. As with the other two carboxyl functional flow control agents in this group of specialty additives, Resiflow L-64F and L-65F, the typical dosage of Resiflow L-66F is 0.2 – 1.5% based on binder solids. Laboratory evaluation is required for each formulation to determine the best processing method and the optimum concentration of the additive.

For powder coating clearcoat applications, Resiflow L-66F is available in several resin masterbatches.

**TYPICAL PROPERTIES\***

Appearance	Clear liquid
Gardner Color	1 max
Non-Volatile, weight %	98.0% minimum

\* Not to be used for specification purposes

**REGULATORY LISTINGS**

The components in this material are either listed or exempt from listing due to polymer exemption criteria for the following chemical listing inventories: AICS (Australia), DSL (Canada), ECL (Korea), ECN (Taiwan), EINECS (Europe), ENCS (Japan), IECSC (China), NZIoC (New Zealand), TSCA (USA)

**PACKAGING (NET WEIGHT)**

44 lb. / 20.0 kg in steel pail  
440 lb. / 199.6 kg in steel drum

**PRODUCT AVAILABILITY**

This product is made to order and requires lead time.

**STORAGE AND HANDLING**

Store in a dry, cool area and avoid excessive heat. Shelf life of unopened containers is one year from date of shipment. Refer to the SDS for additional information.

**CONTACT INFORMATION**

807 N. Main Street  
P.O. Box 127  
Calvert City, KY 42029 USA

(270) 395-4195 PHONE  
(270) 395-5070 FAX

Revision Date: September 12, 2017

TDS Revised by: A. Chizhikova

TDS Approved by: A. Allen